



AURORA ACCESSORIES
WATTS CHECK VALVE

Section 1100 Page 215
 Dated MARCH 2006



Model CVY



Model CVYS

MODEL	SIZE	A	C
CVY	3/8" IPS Threaded	2.19 (55)	1.63 (41)
CVY	1/2" IPS Threaded	2.19 (55)	1.63 (41)
CVY	3/4" IPS Threaded	2.75 (70)	2.00 (50)
CVY	1" IPS Threaded	3.13 (79)	2.25 (57)
CVY	1-1/4" IPS Threaded	3.75 (95)	2.69 (68)
CVY	1-1/2" IPS Threaded	4.31 (108)	3.06 (78)
CVY	2" IPS Threaded	5.06 (129)	3.75 (95)
CVYS	1/2" CxC Solder Connections	2.69 (68)	1.63 (41)
CVYS	3/4" CxC Solder Connections	3.38 (86)	1.94 (49)
CVYS	1" CxC Solder Connections	4.06 (102)	2.25 (57)
CVYS	1-1/4" CxC Solder Connections	4.75 (121)	2.63 (67)
CVYS	1-1/2" CxC Solder Connections	5.38 (137)	3.06 (78)
CVYS	2" CxC Solder Connections	6.69 (168)	3.75 (95)

Bronze body check valve for water or steam service

NOTES:

1. All dimensions in inches (mm), lbs (kg)
2. Dimensions may vary plus minus 1/8 (3)
3. Maximum working pressure: 125 psi (8.6 Bar) WSP, 200 psi (13.8 Bar) WOG non-shook.
4. Maximum working temperature 250 deg F (121 deg C)
5. For additional information visit www.wattsreg.com